

4. Rough Opening: The rough opening should be no more than 1/2" higher and no more than 3/4" wider than the outer dimensions of the door system frame. The rough opening should be no more than 1/8" out of plumb over the height of the opening. The subsill (the lowest horizontal structural member of the rough opening) should be capable of being leveled to within 1/16" over the width of the opening. The subsill should not slope toward the interior of the home.

5. Sill Caulking/ Sealant: Apply three beads of exterior grade polymer-based or polyurethane sealant, 1/2" wide each, along entire rough opening underneath sill.

6. Level, Plumb and Square: Assure that the door system frame is located within the rough opening and shim so that the frame is level, plumb and square. Shim behind each hinge, and on the strike side frame opposite the hinges. Shim behind deadbolt and strike plates.

7. Anchoring: Nail or screw through the door frame and header, do not use the brickmould to anchor the unit to the rough opening. At least one of the fasteners for each of the hinges and all of those on the strike side frame and header locations should penetrate through the door system frame and into the rough opening stud to provide maximum holding strength and secure anchorage.

8. Flashing: Install at the jambs, sill and header as required per manufacturer's instructions or local code requirements to prevent water from penetrating into the wall cavity.

9. Caulking: All joints must be caulked between the rough opening and the door system frame, and between frame members. Caulk carefully between the sill and subfloor to prevent water from entering below the door unit. Fill all gaps of 1/4" or more with filler rod. Caulk all fastener holes. Use only compatible caulking sealants and apply in accordance with the caulking sealant manufacturer's installation instructions.

10. Field Service: It is the responsibility of the installing contractor and painter to fill all nail or screw holes and refinish raw surfaces that result from job fitting, and to clean surfaces prior to finishing.

STAINING & PAINTING INSTRUCTIONS

1. DO NOT sand the Product surface. This could result in damage to the film.

2. Prior to top coating, the surface must be free of dust, dirt, oil, grease and other contaminants. If cleaning is necessary, mild soap and water is recommended.

3. Pre-Finished White Wrapped FrameSaver®: Top coating is not required, however if a coating is desired, follow separately issued Wrapped FrameSaver Finishing Instructions.

4. Stainable Wood Grain Wrapped FrameSaver: Requires top coating per separately issued Wrapped FrameSaver Finishing Instructions. Apply a finish coat before installation or immediately afterwards, but in no case more than 30 days after installation. Direct exposure of unfinished frames to sunlight and weathering may lead to degradation of color and appearance.

5. DO NOT coat weatherstrip or corner pads. Coatings may contain solvents which, when coming in contact with plastics and vinyl used in weatherstripping, can cause these materials to lose their flexible qualities and reduce their performance.

6. Products should be inspected annually to determine condition of the coating. Refinishing of the clear protective coating should be conducted as needed or per the coating manufacturer's recommendations. Any signs of blistering, peeling or cracking the finish should be immediately repaired. Failure to properly maintain the topcoat will result in further coating degradation.

7. Recaulking is required to maintain integrity of joints. Any signs of cracks along joints of the brickmould, jambs, headers or mullions should be resealed with a high-quality exterior caulk.

8. Since many factors influence the appearance and durability of finish coatings, Endura cannot be responsible for coatings applied to Wrapped FrameSaver Products.

Rev 1/7/2019



⚠ WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warning.ca.gov/wood.

Innovation protected under patents and patents pending in U.S. and Canada. See www.EnduraPatents.com

© Endura Products, Inc. All Rights Reserved.



WRAPPED FRAMESAVER®

WOOD MILLWORK COMPONENTS CONSUMER
LIMITED LIFETIME WARRANTY



www.enduraproducts.com

OVERVIEW

This Limited Lifetime Warranty applies to Wrapped FrameSaver® ("Wrapped FrameSaver Products" or "Product") exterior door frames, mullions and brickmould manufactured by Endura Products, Inc. ("Endura").

WHAT THIS WARRANTY COVERS

Subject to the limitations and exclusions below, Endura warrants that Wrapped FrameSaver Products will not rot or decay resulting from water absorption and subsequent fungal damage through the composite bottom of the Product under conditions in which it was originally installed.

Endura also warrants the film as follows:

1. White Prefinished Products

- a. 10-year color fastness (no more than 2 Delta E color change)

2. White Prefinished and Stainable Woodgrain Products

- a. 10 years against film delamination due to adhesive failure
- b. 10 years against film checking or cracking

INSTALLATION SPECIFICATIONS

This Limited Warranty is expressly conditioned upon the installation of Wrapped FrameSaver Products in accordance with Endura's installation instructions and, where applicable, industry-accepted guidelines or local building codes, and that the composite portion of the Wrapped FrameSaver Product extends at least 2-1/2" up from the bottom of each leg. The composite end of the Wrapped FrameSaver Product must be positioned at the bottom of the installed Product.

WARRANTY PERIOD

Lifetime against rot and 10 years on the film as described above from the date that the Product was originally purchased. Fully transferable. Endura also warrants to the original consumer that Wrapped FrameSaver Products will be free from any defects in materials and workmanship, which are not related to rot or decay in the bottom composite portion of the Product or related to the film for a period of one (1) year from the date of manufacture.

EXCLUSIVE REMEDY

In the event that the Wrapped FrameSaver Product fails to meet this Warranty, Endura will (i) replace any defective Product; and (ii) reimburse Warranty Holder for reasonable costs associated with

removal, reinstallation, finishing, freight and/or taxes for the Product.

WARRANTY CLAIMS

If you have a problem with your Wrapped FrameSaver® Product, please contact the dealer/distributor from whom you purchased your Product or contact us directly at:

Mail: Endura Products Customer Service
Phone: (800) 334-2006
 Attn: Wrapped FrameSaver Warranty Claims
Fax: (336) 668-4478
 8817 W. Market St., Colfax, NC 27235
Email: warrantyclaims@enduraproducts.com

You can help us serve you faster by collecting and including the following information:

- Documentation of the Product proof of purchase and purchase date;
- Written description of Product issues or concerns;
- A picture of the defective Product;
- Your name, address where the Products is installed and telephone numbers.

WHAT THIS WARRANTY DOES NOT COVER

This Warranty does not include non-conformities or damages attributed to or arising from:

- Normal wear and tear, or natural weathering of surfaces (other than stated) or applied finishes.
- Rot, decay or fungal damage, for whatever reason, to any portion of the frame other than the composite or film portions of the Product.
- Animal or insect damage.
- Chemical or physical damage.
- Damage or rot to the non-composite, non-film portion due to moisture entrapment between the door panel and frame due to contact between the frame and panel, or between the frame and rough opening.
- Warp within tolerances: bow no more than 7/8" per 6' of length, crook or twist no more than 5/32" per 6' of length, and cup no more than 1/16" per 4" or more of width.
- Product failure due to misuse or abuse; or by alteration or modification of the Product (e.g. machining of the

composite portion of the Wrapped FrameSaver® Product).

- Failure to properly finish/coat Stainable Woodgrain Products prior to installation, but in no case later than 30 days after installation.
- Damage caused by failure to provide ongoing maintenance to the Stainable Woodgrain Product's finish.
- Damage caused by failure to seal all fastener holes through the film.
- Damage caused by cuts or holes which extend through the film.
- Improper installation not in conformance with Endura installation instructions and, where applicable, current industry standards or local building codes.

IMPORTANT LEGAL INFORMATION

THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ANY AND ALL OTHER APPLICABLE WARRANTIES AND REMEDIES. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE APPLICABLE TO WRAPPED FRAMESAVER PRODUCTS IS LIMITED IN DURATION TO THE TERM OF THIS WARRANTY. Some states do not allow limitations on how long an implied warranty or exclusions of limitations of incidental or consequential damages may last, so these limitations may not apply to you. This Warranty gives you specific legal rights. You may have other rights, from state to state.

HANDLING & INSTALLATION REQUIREMENTS

1. Machining: Only the routing of mortises for hinges and locks may be done to the door jambs and mullions. Any trimming or cutting must be done in accordance with Endura's instructions and industry-accepted guidelines. The composite must extend at least 2-1/2" from the bottom face to the bottom of the composite finger joint.

2. Storage: Store only in dry and clean areas. Wood is dimensionally influenced by moisture changes in its surrounding environment. Damp, moist or extremely humid environments may result in excessive warping, twisting or bowing of wood products.

3. Mishandling: Do not drag, scrape or slide the door unit. It should be lifted and carried. Any damage from mishandling of the Products will void this warranty and all future warranty claims.