

Wrapped FrameSaver®

Finishing Instructions

GENERAL NOTES:

- **Pre-Finished White Frames:** Top coating is not required, however if a coating is desired, follow the instructions below.
- **Stainable Wood Grain Frames:** Requires top coating. Apply a finish coat before installation or immediately afterwards. Direct exposure of unfinished frames to sunlight and weathering may lead to degradation of color and appearance.
- DO NOT coat weatherstrip or corner pads. Coatings may contain solvents which, when coming in contact with plastics and vinyl used in weatherstripping, can cause these materials to lose their flexible qualities and reduce their performance.

FRAME PREPARATION:

- DO NOT sand the frame surface. This could result in damage to the wrapping.
- Prior to top coating, the surface must be free of dust, dirt, oil, grease and other contaminants. If cleaning is necessary, mild soap and water is recommended.

FINISHING:

Following the coating manufacturer's recommendations on application techniques and temperatures, drying and recoating times, and application when precipitation is expected. Suggested finishes for each frame option include:

Pre-Finished White Frames:

- Exterior Oil-Base Enamel

Stainable Wood Grain:

- Minwax Gel Stain + Minwax Indoor/Outdoor Helmsman Spar Urethane
- Minwax Pro Series Multi-Surface Wiping Stain + Minwax Pro Series Spar Urethane
- Same-Day® Stain from Therma-Tru

Other brands of finishes may provide acceptable appearance and durability, but evaluation is the responsibility of the user.

MAINTENANCE:

Frames should be inspected annually to determine condition of the coating. Refinishing of the clear protective coating should be conducted as needed or per the coating manufacturer's recommendations. Any signs of blistering, peeling or cracking the finish should be immediately repaired. Failure to properly maintain the topcoat will result in further coating degradation.

DISCLAIMER:

- Since many factors influence the appearance and durability of finish coatings, Endura cannot be responsible for coatings applied to Wrapped FrameSaver® products.